
CROUZET

10 A 4 PDT Non-Latching

Hermetically Sealed Relays



Electrical Control & Protection > Hermetically Sealed Relays > Non-Latching Relays > 10 Amps **> 4 PDT**

Offer Description

- Type: Non-Latching Single Break
- Contact arrangement: 4 PDT
- Nominal Current: 10 A
- Contact Voltage Rating: 28 VDC & 115 VAC 400 Hz / 5V DC to 140 VDC
- Coil Supply: Direct current or alternative current
- Operating power at nominal voltage: 2.7 W to 3 W
- Weight: 70 g to 76 g max
- Polarizing Pin: No

Qualifications

- Aerospace : ASNE0246; ASNE0245 Specification: 421.504/83; ASNE0670 Specification: 482.188/89; EUROCAE ED-14G / DO160G; NF EN ISO 9227; NF EN ISO 2685; ABD0100.1.2; ABD0100.1.8
- Railway : EN 50155; NF CF 62 002; EN 45545-2

Standard Offer

10 A 4 PDT Non-Latching Hermetically Sealed Relays

Coil voltage	New Part Number	Connection		Mounting		Protection	Key	Qualification	Market	P/N
		Type	Material	Flange	Screw					
12 VDC	RN10400 X012D PG0X00	Pin	Gold	-	-	-	-	-	Defense	03265104
	RN10400 X012D PG3K00	Pin	Gold	Horizontal	M3	-	ZUU	NF-62002	Railway	03265907
24 VDC	RN10400 X024D PG3K00	Pin	Gold	Horizontal	M3	-	UUU	NF-62002	Railway	03265060
	RN10400 X024D PT0X 00	Pin	Tin	-	-	-	-	-	Railway	03265302
28 VDC	RN10400 X028D HT1X 00	Hooks	Tin	Horizontal	-	-	-	-	Aerospace	03265021
	RN10400 P028D PG1X 00	Pin	Gold	Horizontal	-	√	-	-	Aerospace	03265110
	RN10400 X028D PG1X 00	Pin	Gold	Horizontal	-	-	-	-	Aerospace	03265117
	RN10400 P028D HT1X 00	Hooks	Tin	Horizontal	-	√	-	-	Aerospace	03265123
	RN10400 X028D PG3X 00	Pin	Gold	Horizontal	M3	-	-	-	Defense	03265168
	RN10400 P028D PG4X 00	Pin	Gold	Horizontal	4/40	√	-	-	Aerospace	03265215
	RN10400 X028D PG4X 00	Pin	Gold	Horizontal	4/40	-	-	ASNE 024628A0	Aerospace	03266016A
	RN10400 P028D PG3X 00	Pin	Gold	Horizontal	M3	√	-	-	Defense	03265203
36 VDC	RN10400 X036D PG3K 00	Pin	Gold	Horizontal	M3	-	YWU	NF-62002	Railway	03265086
	RN10400 X036D PT0X 00	Pin	Tin	-	-	-	-	-	Railway	03265301

Standard Offer

Coil voltage	New Part Number	Connection		Mounting		Protection	Key	Qualification	Market	P/N
		Type	Material	Flange	Screw					
48 VDC	RN10400 X048D PG3K 00	Pin	Gold	Horizontal	M3	-	VUU	NF-62002	Railway	03265059
	RN10400 X048D PT0X 00	Pin	Tin	-	-	-	-	-	Railway	03265303
72 VDC	RN10400 X072D PG3K 00	Pin	Gold	Horizontal	M3	-	WUU	NF-62002	Railway	03265062
	RN10400 X072D PT0X 00	Pin	Tin	-	-	-	-	-	Railway	03265300
110 VDC	RN10400 X110D PG3K 00	Pin	Gold	Horizontal	M3	-	XUU	NF-62002	Railway	03265063
	RN10400 X110D PT0X 00	Pin	Tin	-	-	-	-	-	Railway	03265370
115 VAC	RNH10400 X115A PG4X 00	Pin	Gold	Horizontal	4/40	-	-	ASNE 0246-115B0	Aerospace	03266017A

Accessories

Soldering sockets
P/N: S326 S XX A

For wires or for PCB EN 45545

Sealed sockets
P/N: S326 E XX A
S326 E XX B
S326 E XX D

With crimp contacts EN 45545

Non-Sealed sockets
P/N: S326 P XX A

With crimp contacts EN 45545

Sockets with FASTON lugs
P/N: S326 F XX A

With crimp contacts EN 45545

Contact Rating (A)

Type of Load (High Level)	Minimum operating cycles	28 VDC	115 VAC 400 HZ	72 V
Resistive load	100,000	10 A	10 A	-
Inductive load	20,000	8 A at L/R = 5 ms	8 A at cos φ = 0.75	-
Motor load (Inrush current ≤ 24 A for 20 ms)	100,000	4 A	4 A	-
Lamp load (Inrush current ≤ 24 A for 20 ms)	100,000	2 A	2 A	-
Overload (resistive load)	50	40 A	60 A	-
Resistive load (L/R = 0)	1,000,000 without failure + 1,000,000 with a failure rate < 10^5	-	-	1 A
Inductive load (L/R = 30 ms)	1,000 000 without failure + 1,000,000 with a failure rate < 10^5	-	-	0.5 A
Overload (resistive load at 90VCC max)	100	-	-	1.3 A

Coil Characteristics

Nominal operating voltage	12 VDC	24 VDC	28 VDC	36 VDC	72 VDC	110 VDC	115 VAC 400 Hz
Maximum operating voltage at +70 °C	15 V	33 V	29 V	45 V	90 V	137.5 V	130 V
Minimum operating voltage at +70 °C, coil energized at 1.15 Un during 1h	8.4 V	18.5 V	-	25.2 V	50.4 V	77 V	-
Pick up voltage at +23 °C	6.5 V	14 V	-	20.4 V	38.5 V	68 V	-
Pull in maximum voltage at +20 °C	-	-	13.5 V to 14 V	-	-	-	75 V
Pull in maximum voltage at +125 °C	-	-	19.8 V	-	-	-	100 V
Hold voltage at +20 °C	-	-	7 V	-	-	-	40 V
Hold voltage at +23 °C	3.1 V	6 V	-	10 V	18 V	28 V	-
Drop-out voltage at +23 °C	-	1.8 V	-	2 V	5 V	8 V	-
Drop-out voltage at -25 °C	1 V	1.5 V	-	1.6 V	4 V	6 V	-
Drop-out voltage of -65 °C to +125 °C		-	1.5 V	-	-	-	5 V
Coil resistance in Ohms ± 10% at +20 °C	70 Ω	210 Ω	290 Ω	550 Ω	2,650 Ω	5,000 Ω	3,800 Ω
Maximum back EMF (Volts) with transient suppression	-	-	± 42	-	-	-	-
Rated burden	-	-	-	-	-	-	40 mA


Electrical Characteristics


Voltage drop at nominal current (before life)	150 mV max
Voltage drop at nominal current (after rated life)	175 mV max
Operate time at nominal voltage at 25 °C (DC)	Railway: 15 ms max for DC voltage 10 ms max for DC voltage 15 ms max for AC voltage
Release time at nominal voltage at 25 °C (DC)	Railway: 15 ms max for DC voltage 10 ms max for DC voltage 50 ms max for AC voltage
Bounce time	1 ms max
Dielectric strength at sea level	
Contacts to ground and between contacts	1,250 Vrms / 1,500 Vrms
Coil to ground	1,000 Vrms / 1,500 Vrms
Dielectric strength at 70,000 Ft (all points)	350 Vrms / 500 Vrms
Insulation resistance	
Initial	> 100 mΩ at 500 VDC
After Life Tests	> 50 mΩ at 500 VDC
Low level contact rating	2 mA 30 mVDC
Initial contact resistance	< 15 mΩ
End of life contact resistance	17.5 mΩ

Environmental & Mechanical Characteristics

Temperature range	Aerospace:-55 °C to +125 °C Defense: -65 °C to +125 °C Railway: -40 °C to 85 °C
Operating position	Any
Resistance against vibrations IEC 61373, Category I, Class B, Body mounted EUROCAE ED-14G / DO160G	Sinus: 30 g - 10 - 3,000 Hz Random: 0.4 g²/Hz - 50 - 2,000 Hz Sinus for ASNE: 1.5 g - 10 - 40 Hz 0.7 mm of 40 - 80 Hz 20 g - 80 - 2,000 Hz
Mechanical shock (any axis) IEC 61373, Category I, Class B, Body mounted EUROCAE ED-14G / DO160G	100 g - 6 ms 1/2 sinus
Maximum contact opening time under vibration and shock	10 µs
Shake resistance	40 g
Acceleration	Aerospace & Defense: 20 g all directions Railway: 15 g all directions
Leak rate	≤ $1x10^{-8}$ atm cm³/s
Damp heat	EUROCAE ED-14G / DO160G, IEC 60068-2-78
Salt mist	NF EN ISO 9227, 96 h / IEC 60068-2-11, 96 h
Fire behavior	EUROCAE ED-14G / DO160G + NF EN ISO 2685, EN 45545-2

Mountings







Coding keys for H mounting style


GUIDANCE CODES

U	V	W	X	Y	Z	
						Key 1
						Key 2
						Key 3




Connections






Connection Diagrams

DC



AC



© Crouzet - July 2026 - All rights reserved.
Registered office: 10 rue Docteur Henri Abel 26000 Valence (France) - RCS Romans 663 820 413 - Capital €29.110.000 - **crouzet.com**
Photos by Crouzet.
Registered trademark. Any reproduction, representation or distribution, even in part, is prohibited without prior written permission.

Warning: The technical information contained herein is for informational purposes only and does not constitute a contractual commitment or a guarantee of performance or fitness for any particular purpose. Crouzet and its subsidiaries reserve the right to make any changes without notice. It is essential to consult us regarding any specific use or application of our products, and it is the purchaser's responsibility to verify, in particular through appropriate testing, that the product is suitable for the intended use. Under no circumstances shall our warranty apply, nor shall we be held liable, for any use of our products – including, but not limited to, any modification, addition, or use in combination with other electrical or electronic components, circuits, mounting systems, or any other unsuitable equipment or substance – that has not been expressly approved by us prior to the conclusion of the sale. The applicable contractual terms and conditions are exclusively those set out in the Crouzet proposal accepted by the customer and in the current general terms and conditions of sale.